

### Instructions

- 1. Read the *IAQ*Backgrounder and the Background Information for this checklist.
- 2. Keep the
  Background
  Information and
  make a copy of
  this checklist for
  each ventilation
  unit in your school,
  as well as a
  copy for future
  reference.
- 3. Complete the Checklist.
  - Check the "yes,"
     "no," or
     "not applicable"
     box beside each
     item. (A "no"
     response
     requires further
     attention.)
  - Make comments in the "Notes" section as necessary.
- 4. Return the checklist portion of this document to the IAQ Coordinator.

# **Ventilation Checklist**


TLC IAQ Team

Name:

Sc	hool: 205 Skiff Street, Hamden, CT 06517		
Ur	nit Ventilator/AHU No:  ALL		
Ro	oom or Area: ALL Date Completed: 10-1-2024		
Sid	gnature: Todd A. Solli		
318	gnature.		
1.	OUTDOOR AIR INTAKES		
1a.	Marked locations of all outdoor air intakes on a small floor plan (for	No	N/A
1h	example, a fire escape floor plan)	u	Ц
10.	mode		
	TWINTY 1 OPERANCE ON		
	TIVITY 1: OBSTRUCTIONS  Ensured that outdoor air intakes are clear of obstructions, debris, clogs,		
10.	or covers		
1d.	Installed corrective devices as necessary (e.g., if snowdrifts or leaves		
	frequently block an intake)		
AC	TIVITY 2: POLLUTANT SOURCES		
1e.	Checked ground-level intakes for pollutant sources (dumpsters, loading		
1 f.	docks, and bus-idling areas)		
	toilet, or laboratory exhaust fans; puddles; and mist from		
1 ~	air-conditioning cooling towers)		
ıg.	intakes (e.g., relocated dumpster or extended exhaust pipe)		
	TIVITY 3: AIRFLOW  Obtained chemical smoke (or a small piece of tissue paper or light plastic)		
	Confirmed that outdoor air is entering the intake appropriately		
2.	SYSTEM CLEANLINESS		
	TIVITY 4: AIR FILTERS		
	Replaced filters per maintenance schedule		
2b.	Shut off ventilation system fans while replacing filters (prevents dirt from blowing downstream).		
2c.	Vacuumed filter areas before installing new filters		
2d.	Confirmed proper fit of filters to prevent air from bypassing (flowing		
2e.	around) the air filter		

#### 2. SYSTEM CLEANLINESS (continued)

#### **ACTIVITY 5: DRAIN PANS** 2f. Ensured that drain pans slant toward the drain (to prevent water from Yes No N/A 2g. Cleaned drain pans 2h. Checked drain pans for mold and mildew ...... **ACTIVITY 6: COILS** 2i. Ensured that heating and cooling coils are clean ...... **ACTIVITY 7: AIR-HANDLING UNITS, UNIT VENTILATORS** 2j. Ensured that the interior of air-handling unit(s) or unit ventilator (air-mixing chamber and fan blades) is clean ...... **ACTIVITY 8: MECHANICAL ROOMS** 21. Checked mechanical room for unsanitary conditions, leaks, and spills ....... 2m. Ensured that mechanical rooms and air-mixing chambers are free of trash, 3. CONTROLS FOR OUTDOOR AIR SUPPLY 3a. Ensured that air dampers are at least partially open (minimum position) ...... 3b. Ensured that minimum position provides adequate outdoor air for occupants ...... **ACTIVITY 9: CONTROLS INFORMATION** 3c. Obtained and reviewed all design inside/outside temperature and humidity requirements, controls specifications, as-built mechanical drawings, and controls operations manuals (often uniquely designed) ....... **ACTIVITY 10: CLOCKS, TIMERS, SWITCHES** 3d. Turned summer-winter switches to the correct position ...... 3f. Ensured that settings fit the actual schedule of building use (including night/weekend use) **ACTIVITY 11: CONTROL COMPONENTS** 3g. Ensured appropriate system pressure by testing line pressure at both the 3i. Replaced control system filters at the compressor inlet based on the compressor manufacturer's recommendation (for example, when you 3j. Set the line pressure at each thermostat and damper actuator at the proper **ACTIVITY 12: OUTDOOR AIR DAMPERS** 31. Ensured that the recirculating relief and/or exhaust dampers are visible 3m. Ensured that air temperature in the indoor area(s) served by each outdoor air damper is within the normal operating range .......



*NOTE:* It is necessary to ensure that the damper is operating properly and within the normal range to continue.



3.	CONTROLS FOR OUTDOOR AIR SUPPLY (continued)			
3n.	1 2	Yes		
30	of shutting off appropriate air handler			
50.	when the air handler is turned on			
3p.	If in heating mode, checked that the outdoor air damper goes to its			
	minimum position (without completely closing) when the room			
3 <i>a</i>	thermostat is set to 85°F		_	
<i>J</i> <b>q</b> .	position (without completely closing) when the room thermostat is set	111		
	to 60°F and mixed air thermostat is set to 45°F	. 🛚		
3r.	If the outdoor air damper does not move, confirmed the following items:			
	The damper actuator links to the damper shaft, and any linkage set screws or bolts are tight	X		
	Moving parts are free of impediments (e.g., rust, corrosion)		_	
	• Electrical wire or pneumatic tubing connects to the damper actuator			
	• The outside air thermostat(s) is functioning properly (e.g., in the right			
	location, calibrated correctly)	. 🗶		
Pro	ceed to Activities 13–16 if the damper seems to be operating properly.			
	TIVITY 13: FREEZE STATS			
3s.	Disconnected power to controls (for automatic reset only) to test continuity			
OR	across terminals	. 🛚	ш	
	Confirmed (if applicable) that depressing the manual reset button (usually			
50.	red) trips the freeze stat (clicking sound indicates freeze stat was			
	tripped)	. 🗶		
3u.	Assessed the feasibility of replacing all manual reset freeze-stats with automatic reset freeze-stats	V		
	TE: HVAC systems with water coils need protection from the cold. The freeze			
	e the outdoor air damper and disconnect the supply air when tripped. The ty ge is 35°F to 42°F.	уріса	ı ırıp	,
AC	TIVITY 14: MIXED AIR THERMOSTATS			
	Ensured that the mixed air stat for heating mode is set no higher			
		. 🗶		
3w.	Ensured that the mixed air stat for cooling mode is set no lower than the room thermostat setting	$\nabla$		
	than the room thermostat setting	. 🕰	_	
AC	TIVITY 15: ECONOMIZERS			
3x.	Confirmed proper economizer settings based on design specifications or			
	local practices	. 🗶		
NO	TE: The dry-bulb is typically set at 65°F or lower.			
-	Checked that sensor on the economizer is shielded from direct sunlight	. 🛚		
3z.	Ensured that dampers operate properly (for outside air, return air,			
	exhaust/relief air, and recirculated air), per the design specifications	. 🛚		
NO	TE: Economizers use varying amounts of cool outdoor air to assist with the	cooli	ng	

NOTE: Economizers use varying amounts of cool outdoor air to assist with the cooling load of the room or rooms. There are two types of economizers, dry-bulb and enthalpy. Dry-bulb economizers vary the amount of outdoor air based on outdoor temperature, and enthalpy economizers vary the amount of outdoor air based on outdoor temperature and humidity level.

#### 3. CONTROLS FOR OUTDOOR AIR SUPPLY (continued)

#### **ACTIVITY 16: FANS** 3aa. Ensured that all fans (supply fans and associated return or relief fans) that move outside air indoors continuously operate during occupied Yes No N/A hours (even when room thermostat is satisfied)..... NOTE: If fan shuts off when the thermostat is satisfied, adjust control cycle as necessary to ensure sufficient outdoor air supply. 4. AIR DISTRIBUTION **ACTIVITY 17: AIR DISTRIBUTION** 4a. Ensured that supply and return air pathways in the existing ventilation system 4b. Ensured that passive gravity relief ventilation systems and transfer grilles between rooms and corridors are functioning....... NOTE: If ventilation system is closed or blocked to meet current fire codes, consult with a professional engineer for remedies. 4c. Made sure every occupied space has supply of outdoor air (mechanical system or operable windows) ...... NOTE: If outlets have been blocked intentionally to correct drafts or discomfort, investigate and correct the cause of the discomfort and reopen the vents. 4e. Modified the HVAC system to supply outside air to areas without an outdoor 4f. Modified existing HVAC systems to incorporate any room or zone layout 4g. Moved all barriers (for example, room dividers, large free-standing blackboards or displays, bookshelves) that could block movement of 4h. Ensured that unit ventilators are quiet enough to accommodate classroom 4i. Ensured that classrooms are free of uncomfortable drafts produced by air **ACTIVITY 18: PRESSURIZATION IN BUILDINGS** NOTE: To prevent infiltration of outdoor pollutants, the ventilation system is designed to maintain positive pressurization in the building. Therefore, ensure that the system, including any exhaust fans, is operating on the "occupied" cycle when doing this activity. 4j. Ensured that air flows out of the building (using chemical smoke) through windows, doors, or other cracks and holes in exterior wall (for example, 5. EXHAUST SYSTEMS **ACTIVITY 19: EXHAUST FAN OPERATION** 5a. Checked (using chemical smoke) that air flows into exhaust fan grille(s) .....

If fans are running but air is not flowing toward the exhaust intake, check for the following:

- *Inoperable dampers*
- · Obstructed, leaky, or disconnected ductwork
- Undersized or improperly installed fan
- · Broken fan belt





## 5. EXHAUST SYSTEMS (continued)

#### **ACTIVITY 20: EXHAUST AIRFLOW**

	TE: Prevent migration of indoor contaminants from areas such as bathrooms, ki l labs by keeping them under negative pressure (as compared to surrounding spa		S,
5b.	Checked (using chemical smoke) that air is drawn into the room from adjacent spaces	No	N/A
	nd outside the room with the door slightly open while checking airflow high and door opening (see "How to Measure Airflow").	low ii	n
5c.	Ensured that air is flowing toward the exhaust intake		
AC	TIVITY 21: EXHAUST DUCTWORK		
5d.	Checked that the exhaust ductwork downstream of the exhaust fan (which is under positive pressure) is sealed and in good condition		
6.	QUANTITY OF OUTDOOR AIR		
AC	TIVITY 22: OUTDOOR AIR MEASUREMENTS AND CALCULATIONS		
NO	TE: Refer to "How to Measure Airflow" for techniques.		
6a.	Measured the quantity of outdoor air supplied (22a) to each ventilation unit		
6b.	Calculated the number of occupants served (22b) by the ventilation unit under consideration		
6c.	Divided outdoor air supply (22a) by the number of occupants (22b) to determine the existing quantity of outdoor air supply per person (22c)		
AC	TIVITY 23: ACCEPTABLE LEVELS OF OUTDOOR AIR QUANTITIES		
6d.	Compared the existing outdoor air per person (22c) to the recommended levels in Table 1		
6e.	Corrected problems with ventilation units that supplied inadequate quantities of outdoor air to ensure that outdoor air quantities (22c) meet		

the recommended levels in Table 1 .....

## **NOTES**

Ventilation needs will be addressed by an environmental mechanical engineer

See Walkthrough Checklist for more specifics.